


Webasto Next

Incl. Webasto ChargeConnect



The Webasto Next boasts the following features:

- Scalable charging power up to 11 kW or 22 kW, choice of 4.5 m or 7 m cable length
- Digital management of the charging stations via portal and app with the Webasto backend solution Webasto ChargeConnect
- Always online thanks to 24/7 real-time transmission of the wallbox data to Webasto ChargeConnect
- Authentication at the charging station using Scan & Charge with the Webasto ChargeConnect App
- Energy management system (EMS) integration via Modbus TCP
- Local dynamic load management (stand-alone)*
- Integrated meter module for energy consumption monitoring and reporting
- Clever product design with cable suspension and plug socket
- Cost savings for installation thanks to integrated DC residual current protection
- Remotely addressable by the grid operator via ripple control receiver to ensure grid stability
- User friendly configuration using Wi-Fi hotspot and Webasto Charger Setup App for installers

* Automatically available from Q2 2022 through an over-the-air update

Technical specifications	
Electrical characteristics	
Nominal current (A) (configurable connected load values)	16 or 32 single phase or 3-phase The charging station is configurable in 1A steps
Line voltage (V AC)	230 / 400 (Europe)
Grid frequency (Hz)	50
Grid forms	TN / TT (single phase and 3-phase) IT (only single phase) Splitphase (L1+L2, without N)
EMV class	Emitted interference: Class B (residential, business, commercial areas) Immunity: Industrial areas
Overvoltage category	III as per EN 60664
Protection class	I
Necessary protective equipment	Residual current circuit breaker RCD type A and miniature circuit breakers must be provided on the installation side
Integrated protective equipment	DC residual current protection
Phase rotation	Automatic false phase-sequence detection
Connections	
Mounting	Wall and pole mounting (permanently connected)
Cable feed	Mounted on-wall or in-wall
Connection cross-section (wire dimension)	Cross-section of the connecting cable (Cu) taking into account the local conditions and norms: 6 or 10 mm ² for 16 A and 10 mm ² for 32 A
Charging cable	Type 2 charging cable: up to 32 A / 400 VAC as per EN 62196-1 and EN 62196-2 Length: 4.5 m / 7 m – Integrated cable suspension and plug socket
Output voltage (V AC)	230 / 400
Max. charging capacity (kW)	11 or 22
Communication & features	
Authentication	– “Scan & Charge” via QR code – Webasto ChargeConnect Portal – Webasto ChargeConnect App
Display	RGB-LEDs, buzzer
Network interfaces	– LAN (RJ45) – 10 / 100 Base-TX – WLAN 802.11b/g - 54 Mbit/s – WLAN Hotspot
Communication protocols	OCPP 1.6 J (OCPP 2.0 ready), Modbus TCP
External interfaces	- Addressable via ripple control receiver through dry contacts - Integration into Energy Management Systems (EMS)
Local load management	Dynamic (stand-alone) by integration of an external smart meter*
Mechanical data	
Dimensions (W x H x D) (mm)	225 x 447 x 116
Weight (kg)	11 kW: 4.6 (incl. 4.5 m cable) 5.3 (incl. 7 m cable) 22 kW: 5.7 (incl. 4.5 m cable) 6.8 (incl. 7 m cable)
IP protection class, device	IP54
Protection against mechanical impact	IK08
Ambient conditions	
Installation site	No direct solar radiation
Operating temperature range (°C)	11 kW: -30 to 55 22 kW: -30 to +45
Temperature behavior	A reduction in charging current or shutdown may occur in order to prevent the charging station overheating.
Storage temperature range (°C)	-30 to +80
Permissible relative humidity (%)	5 to 95 non-condensing
Altitude (m)	Max. 3.000 above sea level
Certification compatibility	
Standards and guidelines	– CE conformity – 2014/53/EU Radio Equipment Directive – 2011/65/EU RoHS Directive – 2001/95/EG General Product Safety – 2012/19/EU Waste Electrical and Electronic Equipment Directive – 1907/2006 REACH Regulation
Backend integration	Webasto ChargeConnect, 3rd party backend integration via Weabasto ChargeConnect in preparation
Tested compatible energymangement systems (EMS)	Integration into various energy management systems (EMS) in preparation

* Automatically available from Q2 2022 through an over-the-air update